



Specifications



D.O.D. Product Code 4220

The
S.O.R.D. Elite[®]
Special Operations Recovery Drag

Following are manufacturing specifications for S.O.R.D. Elite units manufactured by American Safety (americansafetyclothingmfg.com).

MATERIALS FOR THE S.O.R.D. ELITE

Core Fabric: Two layers of Kevlar natural woven fabric made from Norfab style #08TT33-60, with binder finish. Fire rated 800° F to 1000° F. Dead lift limit: 4350 lbs.

Webbing: Kevlar filament webbing, black. 2” wide

Sewing Thread: 100% non-ballistic Kevlar spun sewing thread

MATERIALS FOR THE CARRY BAG

Specification: FR Cotton red, approximately 9 to 10 ounces per square yard

Velcro standard Hook & Loop. Webbing/Strapping: Nylon similar to seat belt fabric

WEIGHT: S.O.R.D. Elite 39.9 oz. Carry Bag 9.6 oz. Combined Weight: 49.5 oz.

MANUFACTURING

S.O.R.D. ELITE: Filament webbing is sewn around circumference of woven fabric, including cutout for handles, and the handles themselves. Webbing is overlapped and double stitched for added strength. Includes bar tacking where necessary.

CARRY BAG: FR cotton, pieces cut and sewn together. Velcro and strapping applied. Surged bottom of bag added for extra strength.

EACH S.O.R.D. ELITE AND ITS CARRY BAG ARE SHIPPED AS A SET, WITH THE S.O.R.D. ELITE FOLDED AND INSERTED INTO THE CARRY BAG.

For S.O.R.D. Elite weight carry limitations, see **Certificate of Proof Load**.

THE S.O.R.D. ELITE IS 100% MADE IN THE UNITED STATES OF AMERICA.