



Specifications



D.O.D. Product Code 4220

The **S.O.R.D. Fusion**

Special Operations Recovery Drag

Following are manufacturing specifications for S.O.R.D. Fusion units manufactured by American Safety (americansafetyclothingmfg.com).

MATERIALS FOR THE S.O.R.D. FUSION

Core Fabric: 100% non-ballistic Kevlar natural woven fabric made from Norfab style #08TT33-60, with binder finish. Fire rated 800° F to 1000° F. Dead lift limit: 4550 lbs.

Sewing Thread: 100% non-ballistic Kevlar spun sewing thread.

Webbing: Nylon strap webbing similar to seatbelt fabric. Black. 2” wide.

MATERIALS FOR THE S.O.R.D. FUSION CARRY BAG

Specification: FR Cotton red, approximately 9 to 10 ounces per square yard

Velcro standard Hook & Loop

Webbing/Strapping: Nylon, similar to seat belt fabric.

WEIGHT: S.O.R.D. Fusion 39.9 oz. Carry Bag 9.6 oz. Combined Weight: 49.5 oz.

MANUFACTURING

S.O.R.D. FUSION: Nylon strap webbing is sewn around circumference of woven fabric, including cutout for handles, and the handles themselves. Webbing is overlapped and double stitched for added strength. Includes bar tacking where necessary.

CARRY BAG: FR cotton, pieces cut and sewn together. Velcro and strapping applied. Surged bottom of bag added for extra strength.

EACH S.O.R.D. FUSION AND ITS CARRY BAG ARE SHIPPED AS A SET, WITH THE S.O.R.D. FUSION FOLDED AND INSERTED INTO THE CARRY BAG.

For S.O.R.D. Fusion weight carry limitations, see **Certificate of Proof Load**.

THE S.O.R.D. FUSION IS 100% MADE IN THE UNITED STATES OF AMERICA.